## The very powerful, long-life, low-noise high-pressure washer. With long hose range for larger cleaning tasks

This very powerful Nilfisk easily handles larger and frequent cleaning tasks.

From gentle cleaning of more soft or sensitive surfaces to blasting away ingrained dirt.

It has a long-lasting induction motor and offers a large range of operation with its 10m steel armed hose.

It is equiped with many invaluable features, when you need to work for longer periods of time; telescopic handle, sturdy wheels, long hose and one-hand operated hose reel as well as a rubber suspension to ensure lower noise.

To increase performance, this Nilfisk comes with Click&Clean connectivity for a range of optional accessories.

- · 160 bar, max pressure
- · Sturdy build with aluminum pump and long-life induction motor
- Automatic start/ stop system
- 10m reinforced steelarmed hose and one-hand operated hose reel
- · Telescopic handle with sturdy handle and aluminum tubes
- · Rubber suspension ensures a lower noise when working
- · Easy storage of gun, lance, nozzles and foam sprayer onboard
- Convenient storage of electric cable
- · Click&Clean nozzle system ensures quick and easy change of nozzle.
- The X-TRA model features a built-in trolley for increased mobility.
- · Can be used as stationary machine with optional wall hook

### Standard equipment

Included accessories		Ref. no.	Min. required	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X-TRA EU
Hose and Co	nnection					
	10M SUPERFLEX HOSE	128500082	0	•	•	•
	G4 NOZZLE TUBE	128500669	0	•	•	•
Nozzle - High	Pressure Washer					
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•	•
Brush		'				
	ROTARY BRUSH	126411395	0			
Accessory						
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	CLEANING TOOL BLACK	6520844	0	•	•	•



# The very powerful, long-life, low-noise high-pressure washer. With long hose range for larger cleaning tasks

	Included accessories	Ref. no.	Min. required	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X-TRA EU
9	DRAIN AND TUBE 8M	128500461	0			
	G5 SPRAY HANDLE	128500072	0	•	•	•
	NILFISK PATIO ACCESSORY	128500702	0			•

#### Standard equipment

	Included accessories	Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
Hose and Co	proction		. oqu ou	EU
Hose and Col	inection			
0	10M SUPERFLEX HOSE	128500082	0	•
	G4 NOZZLE TUBE	128500669	0	•
Nozzle - High	Pressure Washer			
	PR TORNADO RED2 LINES CLICK	128500657	0	•
Brush				
	ROTARY BRUSH	126411395	0	•
Accessory				
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•
	CLEANING TOOL BLACK	6520844	0	•



The very powerful, long-life, low-noise high-pressure washer. With long hose range for larger cleaning tasks

	Included accessories	Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
9	DRAIN AND TUBE 8M	128500461	0	•
	G5 SPRAY HANDLE	128500072	0	•
7	NILFISK PATIO ACCESSORY	128500702	0	•

Model	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X- TRA EU
Ref. no.	128471196	128471195	128471197
PRODUCT FEATURES			
Trolley	•	•	•
Hose reel	•	•	•
Aluminium pump	•	•	•
Lance and spray gun storage	•	•	•
Storage of accessories	•	•	•
Cable storage	•	•	•
Click&Clean (C&C) nozzle concept	•	•	•
Gun with quick connection and swivel	•	•	•
Superflex (steel armed) hose	•	•	•
Automatic start/stop	•	•	•
Soft grip	•	•	•
Telescopic handle	•	•	•
Pressure regulation in nozzle	•	•	•

Model E 160.1-10 PADH X-TRA EU

Ref. no. 128471198

### PRODUCT FEATURES

Trolley	•
Hose reel	•
Aluminium pump	•
Lance and spray gun storage	•
Storage of accessories	•
Cable storage	•



PRODUCT FEATURES	Model			E 160.1-10 PADH X- TRA EU
Cilck&Clean (C&C) nozzle concept         •           Gun with quick connection and swivel         •           Superflex (steel armed) hose         •           Automatic start/stop         •           Soft grip         •           Telescopic handle         •           Pressure regulation in nozzle         •           Technical specifications         E 160.1-10 H X-TRA         E 160.1-10 H X	Ref. no.			128471198
Gun with quick connection and swive!         •           Superflex (steel armed) hose         •           Automatic start/stop         •           Soft grip         •           Telescopic handle         •           Pressure regulation in nozzle         •           Technical specifications         E 160.1-10 H X-TRA LV         Max 160/ max 16         Max 160/ max 16         Max 160/ max 16         Max 160/ max 16         Automax 16	PRODUCT FEATURES			
Superflex (steel armed) hose         •           Automatic start/stop         •           Soft grip         •           Telescopic handle         •           Pressure regulation in nozzle         •           Technical specifications         E 160.1-10 H X-TRA         E 160.1-10 H X-TRA         E 160.1-10 PH X-TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         Max 160/ max 16         Max 160/ max 16           Voltage (V)         230-240         230-240         230-240           Rated power (kW)         2.3         2.3         2.3           Power consumption (A)         10.5         10.5         10.5           Water flow Qmax/Qiec (Vh)         500 / 410         500 / 410         500 / 410           Max. inlet temperature (°C)         40         40         40           Max. inlet temperature (°C)         40         40         40           Weight (kg)         20.6         20.6         20.6           Technical specifications         E 160.1-10 PAD X-TRA EU         TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         20.2           Voltage (V)         230-240         230-240           Rated power (kW)         2.3         230-240           Wa	Click&Clean (C&C) nozzle concept			•
Automatic start/stop  Soft grip  Telescopic handle  Pressure regulation in nozzle  Technical specifications  E 160.1-10 H X-TRA UK  TRAE UF  Max 160/ max 16  Max 160/ max 16  Max 160/ max 16  Max 160/ max 16  To 10, 10, 10  To 10  Max. inlet temperature (°C)  Technical specifications  Technical spe	Gun with quick connection and swivel			•
Soft grip         •           Telescopic handle         •           Pressure regulation in nozzle         •           Technical specifications         \$\begin{cases} \text{Ed0.1-10 H X-TRA} & \text{Ed0.1-10 H X-TRA} & \text{Ed0.1-10 H X-TRA} & \text{Ed0.1-10 PM X-TRA EUV}           Pump pressure (bar/MPa)         Max 160/ max 16 & Max 160/ ma	Superflex (steel armed) hose			•
Telescopic handle         •           Pressure regulation in nozzle         E 160.1-10 H X-TRA         Max 160 / max 16         20.240         230-240 <td>Automatic start/stop</td> <td></td> <td></td> <td>•</td>	Automatic start/stop			•
Pressure regulation in nozzle  Technical specifications  E 160.1-10.H X-TRA  E160.1-10.H X-TRA  E 160.1-10.H X-TRA  E 1 60.1-10.H X-TRA  E 1 60.1-10	Soft grip			•
Technical specifications         E 160.1-10 H X-TRA UK         E 160.1-10 H X-TRA EU         E 160.1-10 H X-TRA EU           Pump pressure (bar/MPa)         Max 160 / max 16         230-240         230-240         230-240         230-240         230-240         230-240         23         2.3         2.3         2.3         2.3         2.3         2.3         2.3         2.3         2.3         2.3         2.0         200 / 410         500 / 410         500 / 410         500 / 410         500 / 410         500 / 410         500 / 410         500 / 410         40	Telescopic handle			•
Name	Pressure regulation in nozzle			•
Voltage (V)         230-240         230-240         230-240           Rated power (kW)         2.3         2.3         2.3           Power consumption (A)         10.5         10.5         10.5           Water flow Qmax/Qiec (l/h)         500 / 410         500 / 410         500 / 410           Hose length (m)         10         10         10           Max. inlet temperature (°C)         40         40         40           Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         20.6         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU         TRA EU         TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         20.2         20.240           Rated power (kW)         2.3         2.3         2.3           Power consumption (A)         10.5         500 / 410           Hose length (m)         10         500 / 410           Max. inlet temperature (°C)         40         40	Technical specifications			
Rated power (kW)         2.3         2.3         2.3           Power consumption (A)         10.5         10.5         10.5           Water flow Qmax/Qiec (l/h)         500 / 410         500 / 410         500 / 410           Hose length (m)         10         10         10           Max. inlet temperature (°C)         40         40         40           Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         20.6         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU         TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         Voltage (V)         230-240           Rated power (kW)         2.3         2.3           Power consumption (A)         10.5         500 / 410           Hose length (m)         10         500 / 410           Max. inlet temperature (°C)         40         40	Pump pressure (bar/MPa)	Max 160/ max 16	Max 160/ max 16	Max 160/ max 16
Power consumption (A)         10.5         10.5         10.5           Water flow Qmax/Qiec (I/h)         500 / 410         500 / 410         500 / 410           Hose length (m)         10         10         10           Max. inlet temperature (°C)         40         40         40           Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU         TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         Voltage (V)           Rated power (kW)         2.3         20.240           Power consumption (A)         10.5         500 / 410           Hose length (m)         10         40	Voltage (V)	230-240	230-240	230-240
Water flow Qmax/Qiec (I/h)         500 / 410         500 / 410         500 / 410           Hose length (m)         10         10         10           Max. inlet temperature (°C)         40         40         40           Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU         TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16         230-240           Voltage (V)         2.3         2.3           Power consumption (A)         10.5         500 / 410           Hose length (m)         10         40           Max. inlet temperature (°C)         40         40	Rated power (kW)	2.3	2.3	2.3
Hose length (m) 10 10 10  Max. inlet temperature (°C) 40 40 40 40  Dimensions (L x W x H) (mm) 395 x 345 x 900 395 x 345 x 900 395 x 345 x 900  Weight (kg) 20.6 20.6 20.6  Technical specifications  E 160.1-10 PADH X-TRA EU  Pump pressure (bar/MPa) Max 160/ max 16  Voltage (V) 230-240  Rated power (kW) 2.3  Power consumption (A) 10.5  Water flow Qmax/Qiec (I/h) 500 / 410  Hose length (m) 10  Max. inlet temperature (°C) 40	Power consumption (A)	10.5	10.5	10.5
Max. inlet temperature (°C)         40         40         40           Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x	Water flow Qmax/Qiec (I/h)	500 / 410	500 / 410	500 / 410
Dimensions (L x W x H) (mm)         395 x 345 x 900         395 x 345 x 900         395 x 345 x 900           Weight (kg)         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16           Voltage (V)         230-240           Rated power (kW)         2.3           Power consumption (A)         10.5           Water flow Qmax/Qiec (l/h)         500 / 410           Hose length (m)         10           Max. inlet temperature (°C)         40	Hose length (m)	10	10	10
Weight (kg)         20.6         20.6         20.6           Technical specifications         E 160.1-10 PADH X-TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16           Voltage (V)         230-240           Rated power (kW)         2.3           Power consumption (A)         10.5           Water flow Qmax/Qiec (I/h)         500 / 410           Hose length (m)         40	Max. inlet temperature (°C)	40	40	40
Technical specifications         E 160.1-10 PADH X-TRA EU           Pump pressure (bar/MPa)         Max 160/ max 16           Voltage (V)         230-240           Rated power (kW)         2.3           Power consumption (A)         10.5           Water flow Qmax/Qiec (l/h)         500 / 410           Hose length (m)         10           Max. inlet temperature (°C)         40	Dimensions (L x W x H) (mm)	395 x 345 x 900	395 x 345 x 900	395 x 345 x 900
Pump pressure (bar/MPa)  Max 160/ max 16  Voltage (V)  Rated power (kW)  Power consumption (A)  Water flow Qmax/Qiec (l/h)  Hose length (m)  Max. inlet temperature (°C)  TRA EU  Max 160/ max 16  230-240  10.5  500 / 410  40	Weight (kg)	20.6	20.6	20.6
Voltage (V)       230-240         Rated power (kW)       2.3         Power consumption (A)       10.5         Water flow Qmax/Qiec (I/h)       500 / 410         Hose length (m)       10         Max. inlet temperature (°C)       40	Technical specifications			
Rated power (kW)       2.3         Power consumption (A)       10.5         Water flow Qmax/Qiec (I/h)       500 / 410         Hose length (m)       10         Max. inlet temperature (°C)       40	Pump pressure (bar/MPa)			Max 160/ max 16
Power consumption (A) 10.5  Water flow Qmax/Qiec (I/h) 500 / 410  Hose length (m) 10  Max. inlet temperature (°C) 40	Voltage (V)			230-240
Water flow Qmax/Qiec (I/h)       500 / 410         Hose length (m)       10         Max. inlet temperature (°C)       40	Rated power (kW)			2.3
Hose length (m) 10  Max. inlet temperature (°C) 40	Power consumption (A)			10.5
Max. inlet temperature (°C) 40	Water flow Qmax/Qiec (I/h)			500 / 410
	Hose length (m)			10
Dimensions (L x W x H) (mm) 395 x 345 x 900	Max. inlet temperature (°C)			40
	Dimensions (L x W x H) (mm)			395 x 345 x 900
Weight (kg) 20.6	Weight (kg)			20.6



The very powerful, long-life, low-noise high-pressure washer. With long hose range for larger cleaning tasks

 $\bullet$  Standard equipment,  $^{\bigcirc}$  Supplementary accessories,  $^{\square}$  Mountable equipment

	Accessories	Ref. no.	Min. required	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X-TRA EU
Accessory Kit						
	MULTI BRUSH KIT	128470459	0	0	0	0
°0000	O-RING KIT CONSUMER HPW	128500292	0	0	0	0
Accessory		'				
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
	CLEANING TOOL BLACK	6520844	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	0
0	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	0	0
	G5 SPRAY HANDLE	128500072	0	•	•	•
	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI BRUSH	128470456	0	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
7	NILFISK PATIO ACCESSORY	128500702	0	0	0	•



	Accessories	Ref. no.	Min. required	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X-TRA EU
19	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0
Ä	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ø	VSB SET - GREEN	6410891	0	0	0	0
	WALL HOOK	106411386	0	0	0	0
6	WATER SUCTION KIT	126411387	0	0	0	0
Hose and Co	nnection					
0	10M SUPERFLEX HOSE	128500082	0	•	•	•
0	EXTENSION HOSE STEEL ARMED 7 M	6411048	0	0	0	0
	G4 NOZZLE TUBE	128500669	0	•	•	•
Nozzle - High	Nozzle - High Pressure Washer					
	C&C CAR NOZZLE	6411136	0	0	0	0



	Accessories	Ref. no.	Min. required	E 160.1-10 H X-TRA UK	E160.1-10 H X-TRA EU	E 160.1-10 PH X-TRA EU
	PR TORNADO RED2 LINES CLICK	128500657	0	•	•	•
9	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	0
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
	Car brush head	128500463	0	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0
	Garden brush head	128470457	0	0	0	0
	ROTARY BRUSH	126411395	0	0	0	0
3	ROTARY BRUSH	6410762	0	0	0	0

ullet Standard equipment, ullet Supplementary accessories, ullet Mountable equipment

	Accessories	Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
Accessory Kit				
	MULTI BRUSH KIT	128470459	0	0
0000	O-RING KIT CONSUMER HPW	128500292	0	0
Accessory				



	Accessories	Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•
	CLEANING TOOL BLACK	6520844	0	•
9	DRAIN AND TUBE 8M	128500461	0	•
O	DRAIN AND TUBE CLEANER ALTO	6410766	0	0
	G5 SPRAY HANDLE	128500072	0	•
	INLET SUCTION HOSE 3M	128500673	0	o
	MULTI BRUSH	128470456	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0
7	NILFISK PATIO ACCESSORY	128500702	0	•
19	NILFISK POWER PATIO	128500955	0	0
	NILFISK WATER FILTER	128500674	0	0
	ROOF CLEANER	128470040	0	0



	Accessories	Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
	UNDERCHASSIS SPRAY LANCE	6410763	0	0
<b>Ø</b>	VSB SET - GREEN	6410891	0	0
	WALL HOOK	106411386	0	0
6	WATER SUCTION KIT	126411387	0	0
Hose and Connection				
	10M SUPERFLEX HOSE	128500082	0	•
0	EXTENSION HOSE STEEL ARMED 7 M	6411048	0	0
	G4 NOZZLE TUBE	128500669	0	•
Nozzle - High Pressure Washer				
<b>8</b>	C&C CAR NOZZLE	6411136	0	0
	PR TORNADO RED2 LINES CLICK	128500657	0	•
9	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0
Brush				
	AUTOBRUSH ALONE	6411131	0	0



Accessories		Ref. no.	Min. required	E 160.1-10 PADH X-TRA EU
	Car brush head	128500463	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0
	Garden brush head	128470457	0	0
	ROTARY BRUSH	126411395	0	•
3	ROTARY BRUSH	6410762	0	0

