This high-pressure washer offers great performance and durability with a long lasting induction motor. It easily handles larger and frequent cleaning tasks and ranges from the gentle cleaning of more soft or sensitive surfaces to blasting away ingrained dirt.

The large handle, sturdy wheels and long hose all ensure the ease-of-use you want, when working for longer periods of time. To increase performance, this Nilfisk comes with Click&Clean connectivity for a range of optional accessories.

- 135 max pressure.
- Sturdy design with aluminum pump and long-life induction motor.
- Handles moderate to tough dirt on surfaces up to 30 m2/ hour.
- Automatic start/ stop system.
- Low noise.
- Trolley for high mobility.
- 6 or 8m high-pressure hose
- Hose reel for convenient storage of hose.
- Easy storage of gun, lance, nozzle and foam sprayer.
- Click&Clean connectivity for quick and easy change of nozzles.

● Standard equipment							
	Included accessories	Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK	
Hose and Co	Hose and Connection						
0	8M STANDARD HOSE	128500080	0		•		
Q	HOSE 6M	126481138	0	•		•	
Nozzle - High	Pressure Washer						
	PR TORNADO TURQUOISE	126481118	0	•	•	•	
Brush							
	FIXED BRUSH SHORT NILFISK SP	128500685	0				
Accessory							
Ĩ	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•	
9	DRAIN AND TUBE 8M	128500461	0				



The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

Included accessories		Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•	•
	G3 LANCE COMPLETE	126481134	0	•	•	•
2	NILFISK PATIO ACCESSORY	128500702	0			•

Standard equipment

	Included accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
Hose and Co	nnection					
0	8M STANDARD HOSE	128500080	0		•	
Q	HOSE 6M	126481138	0	•		•
Nozzle - High	Pressure Washer					
	PR TORNADO TURQUOISE	126481118	0	•	•	•
Brush						
	FIXED BRUSH SHORT NILFISK SP	128500685	0			•
Accessory						
Ĩ	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0			•



The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

	Included accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•	•
	G3 LANCE COMPLETE	126481134	0	•	•	•
5	NILFISK PATIO ACCESSORY	128500702	0			•

Standard equipment

	Included accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
Hose and Co	nnection				
0	8M STANDARD HOSE	128500080	0		•
Q	HOSE 6M	126481138	0	•	
Nozzle - High	Pressure Washer				
	PR TORNADO TURQUOISE	126481118	0	•	•
Brush					
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	•
Accessory					
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
9	DRAIN AND TUBE 8M	128500461	0	•	•



	Included accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•
	G3 LANCE COMPLETE	126481134	0	•	•
2	NILFISK PATIO ACCESSORY	128500702	0	•	•

Model	C 135.1-6I X-TRA UK	C 135.1-8I X-TRA UK	C 135.1-6i P X-TRA UK
Ref. no.	128471171	128471173	128471174
PRODUCT FEATURES			

Trolley	•	•	•
Cable holder	•	•	•
Hose reel	•	•	•
Aluminium pump	•	•	•
Lance and spray gun storage	•	•	•
Storage of accessories	•	•	•
Click&Clean (C&C) nozzle concept	•	•	•
Gun with quick connection and swivel	•	•	•
Automatic start/stop	•	•	•
Pressure regulation in nozzle	•	•	•

Model	C 135.1-6I X-TRA EU	C 135.1-8I X-TRA EU	C 135.1-6i PAD X- TRA EU
Ref. no.	128471170	128471172	128471204
PRODUCT FEATURES			
Trolley	•	•	•

Cable holder	•	•	•
Hose reel	•	•	•
Aluminium pump	•	•	•
Lance and spray gun storage	•	•	•
Storage of accessories	•	•	•
Click&Clean (C&C) nozzle concept	•	•	•
Gun with quick connection and swivel	•	•	•
Automatic start/stop	•	•	•



The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

Raf. no.12847117012847117212847128PRODUCT FEATURESPressure regulation in nozzie•••Model1381-16/ PANC1381-16/ PANC1381-16/ PANRef. no.128471205128471205128471205PRODUCT FEATURES•••Toiley•••Cable holder•••Hose real•••Lance and spray gun storage•••Storage of accessories•••Citck Clon Cock on coret•••Valutantict startstop•••Pressure regulation in nozzie*••Pressure regulation in nozzie*••Pressure regulation in nozzie*••Pressure regulation in nozzie**•Pressure regulation in nozzie**•Pressure regulation in nozzie**•Pressure regulation in nozzie***Pressure regulation in nozzie*** <tr<< th=""><th>Model</th><th>C 135.1-6I X-TRA EU</th><th>C 135.1-8I X-TRA EU</th><th>C 135.1-6i PAD X- TRA EU</th></tr<<>	Model	C 135.1-6I X-TRA EU	C 135.1-8I X-TRA EU	C 135.1-6i PAD X- TRA EU
Pressure regulation in nozzie••ModelC135:1-61 PAD X: TTAK UKC135:1-61 PAD X: TTAK UKC135:1-61 PAD X: TTAK UKRef. no.126471205126471205PRODUCT FEATURESToilayCable holderHoes reelAuminium pumpLance and spray gun storageStorage of accessoriesClick&Clean (C&C) nozzic conceptQun with quick connection and swivelAutomatic start/stopPressure regulation in nozzieC131:161/LTRC131:161/LTRC131:161/LTRPump pressure (bar/MPA)Max 135 / max 135Max 135 / max 135Max 135 / max 135Voltage (V)230230230230Rated power (KW)1.71.77.7Power consumption (A)400400400Max intert emperature (°C)400400400Mare flaw Gradifications1.61.61.6Max intert emperature (°C)305 225 x885305 225 x885305 225 x885Negler (My)1.51.51.51.5Pump pressure (bar/MPA)1.61.61.61.6Max intert emperature (°C)305230230230Mater flaw Gradifications1.51.51.51.5Pump ressure (bar/MPA) <t< td=""><td>Ref. no.</td><td>128471170</td><td>128471172</td><td>128471204</td></t<>	Ref. no.	128471170	128471172	128471204
Model C 135,14) PAD. C 135,14) PAD. Ref. no. 128471205 128471205 PRODUCT FEATURES - - Tolley - - Cable holder - - Auminium pump - - Lance and spray gun storage - - Storage of accessories - - Click&Clean (CAC) nozzle concept - - Gun with quick connection and swivel - - Automatic start/stop - - Pressure regulation in nozzle - - Technical specifications Cli35,161,XTRA Cli35,161,XTRA Pump pressure (bar/MPA) Atal 35 max1.5 Max1.55 Volage (V) 20 20 Reade power (WA) 7.4 7.4 Volage (Lay XTMA) 440/380 440/380 Reade power (WA) 1.5 1.5 Pump pressure (bar/MPA) 6 8 6 Maxin flow Charch(Lay XTMA) 7.4 7.4 7.4 P	PRODUCT FEATURES			
Model TTR L IK TTR A EU Ref. no. 128471205 128471205 PRODUCT FEATURES - - Talley - - Cable holder - - Hose real - - Autonitum pump - - Lance and spray gun storage - - Storage of accessories - - Click&Clean (CAC) nozzle concept - - Gun with quick connection and swivel - - Automatic start/storp - - - Pressure regulation in nozzle Cli3S Lifel X-TRA Max155 max15 Max155 max15 Max155 max15 Pump pressure (bar/MPA) Atal 35 max15 Max155 max15 Max155 max15 Max155 max15 Power consumption (A) T,4 T,4 T,4 T,4 Water flow Quax/Qiec (M) Afd Afd Afd Maxer flow Quax/Qiec (M) Afd Afd Afd Maxer flow Quax/Qiec (M) Afd Afd Afd	Pressure regulation in nozzle	•	•	•
PRODUCT FEATURES Troley • •	Model			
Tolley - - Cable holder - - Hose reel - - Auminium pump - - Lance and spray gun storage - - Storage of accessories - - Click&Clean (C&C) nozzle concept - - Gun with quick connection and swivel - - Automatic start/stop - - Pressure regulation in nozzle - - Technical specifications Cli5s:1/6! X-TRA Cl3s:1/6! X-TRA Max 135 / max 13.5 Voltage (V) 230 230 230 Valer flow Omax/Qice (I/h) 17 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Valer flow Omax/Qice (I/h) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 15.8 Technical specifications Class: 16! X-TRA Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 230 Ratel power (kW) 1.7 1.7 <td< td=""><td>Ref. no.</td><td></td><td>128471205</td><td>128471206</td></td<>	Ref. no.		128471205	128471206
Cable holderHose realAlurinitum pumpLance and spray gun storageStorage of accessoriesClick&Clean (C&C) nozzle conceptGun with quick connection and swivel	PRODUCT FEATURES			
Hose real	Trolley		•	•
Aluminium pump • • Lance and spray gun storage • • Storage of accessories • • Click&Clean (C&C) nozzle concept • • Gun with quick connection and swivel • • Automatic start/stop • • Pressure regulation in nozzle • • Technical specifications Cli35.1-6l X-TRA Cli35.1-6l X-TRA Cli35.1-6l X-TRA Voltage (V) Max 135 / max 13.5 Voltage (V) 230 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qice (th) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Velight (kg) 15.8 15.8 15.8 15.8 Technical specifications Cli35.1-6l X-TRA Max 135 / max 13.5 Volage (V) 16 8 <td>Cable holder</td> <td></td> <td>•</td> <td>•</td>	Cable holder		•	•
Lance and spray gun storage • • Storage of accessories • • Click&Clean (C&C) nozzle concept • • Gun with quick connection and swivel • • Automatic start/stop • • Pressure regulation in nozzle • • Technical specifications C135.1-61 X-TRA C135.1-81 X-TRA C135.1-81 X-TRA Voltage (V) 230 230 230 Rade power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Valter flow Qmax/Qice (//h) 400 305 x295 x885 305 x295 x885 Veight (kg) 15.8 15.8 15.8 Technical specifications C135.1-61 X-TRA Max 135 / max 13.5 Max 135 / max 13.5 Max intel temperature (°C) 4400 380 4400 380 4400 380 Veight (kg) 15.8 15.8 15.8 Technical specifications C135.1-61 X-TRA Max 135 / max 13.5 Max 135 / max 13.5 Veight (kg) 15.8 15.8 15.8 15.8 Technical specifications	Hose reel		•	•
Storage of accessories • • Click&Clean (C&C) nozzle concept • • Gun with quick connection and swivel • • Automatic start/stop • • Pressure regulation in nozzle • • Technical specifications Cl 35.1-6l X-TRA Cl 35.1-8l X-TRA Cl 35.1-8l X-TRA Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Vater flow Qmax/Qiec (l/h) 400 400 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Technical specifications Cl 35.1-6l X-TRA Cl 35.1-6l X-TRA Voltage (V) 2.00 2.00 2.00 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Pump pressure (bar/MPa)<	Aluminium pump		•	•
Click&Clean (C&C) nozzle concept • • Gun with quick connection and swivel • • Automatic start/stop • • Pressure regulation in nozzle • • Technical specifications Cli35.1 ₆ l X-RRA Cli35.1 ₆ l X-RA Cli35.1 ₆ l X-RA Pump pressure (bar/MPa) Max 135 / max1.35 Max 135 / max1.35 Max135 / max1.35 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Vater flow Qmax/Qiec (t/h) 400 400 400 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Technical specifications Cli35.1 ₆ l X-RA Auto 135 Pump pressure (bar/MPa) Max 135 / max1.3 Max135 / max1.3 Vatigt (kg) 15.8 15.8 15.8 Technical specifications Cli35.1 ₆ l X-RA Auto 135 Voltage (V) 230 230 230 Vatige (tki) 1.7	Lance and spray gun storage		•	•
Gun with quick connection and swivel • • Automatic start/stop · • Pressure regulation in nozzle · • Technical specifications C135.1-61X.TRA C135.1-61X.TRA C135.1-61X.TRA Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440 / 380 440 / 380 440 / 380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Red power (kW) 1.7 1.7 1.7 Voltage (V) 230 230 230 Voltage (V) 230	Storage of accessories		•	•
Automatic start/stop • • Pressure regulation in nozzle • • Technical specifications C135.1-61 X-TRA C135.1-81 X-TRA C135.1-81 X-TRA Pump pressure (bar/MPa) Max 135 / max1.35 Max 135 / max1.35 Max 135 / max1.35 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (/h) 440/380 440/380 440/380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Pump pressure (bar/MPa) Max 135 / max1 3.5 Max135 / max1 3.5 Pump pressure (bar/MPa) Max135 / max1 3.5 Max135 / max1 3.5 Voidage (V) 230 230 230 Pump pressure (bar/MPa) Max135 / max1 3.5 Max135 / max1 3.5 Voidage (V) 230 230 230 Quart (bar (MP) 1.7 1.7 Voidage (V) 2.30	Click&Clean (C&C) nozzle concept		•	•
Pressure regulation in nozzle••Technical specificationsC135.1-61 X-TRAC135.1-61 X-TRAC135.1-61 X-TRAPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Vater flow Qmax/Qiec (I/h)440/380440/380440/380Hose length (m)686Max. inlet temperature (°C)404040Dimensions (L x W x H) (mm)305 x 295 x 885305 x 295 x 885305 x 295 x 885Veight (kg)15.815.815.815.8Technical specificationsC135.1-61 X-TRAMax 135 / max 13.5Max 135 / max 13.5Pump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5305 x 295 x 885Voltage (V)230230230Rated power (kW)1.71.71.7Pump ressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Vater flow Qmax/Qiec (I/h)440/380440/380	Gun with quick connection and swivel		•	•
Technical specifications C 135.1-61 X-TRA Luk Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 230 230 Rated power (kW) 1.7 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 7.4 Vater flow Qmax/Qiec (l/h) 440/380 440/380 440/380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 15.8 Technical specifications Kat 35 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 230 Rated power (kW) 1.7 1.7 1.7	Automatic start/stop		•	•
Technical specifications UK UK UK Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qice (l/h) 440/ 380 440/ 380 440/ 380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Weight (kg) 15.8 15.8 15.8 Fechnical specifications C135.1-61 X-TRA EU Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7	Pressure regulation in nozzle		•	•
Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440/380 440/380 440/380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Technical specifications C135 Ligl X-TRA C135 Ligl X-TRA Voltage (V) 230 230 230 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440/380 440/380 440/380	Technical specifications			
Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440/380 440/380 440/380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Veight (kg) 15.8 15.8 15.8 Technical specifications C135 1-61 X-TRA C135 1-61 X-TRA Ax135 / max13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440/380 440/380 440/380	Pump pressure (bar/MPa)	Max 135 / max 13.5	Max 135 / max 13.5	Max 135 / max 13.5
Power consumption (A) 7.4 7.4 Water flow Qmax/Qiec (I/h) 440/ 380 440/ 380 440/ 380 Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Weight (kg) 15.8 15.8 15.8 Technical specifications C135.1 eB X-TRA C135.1 eB X-TRA Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (I/h) 440/ 380 440/ 380 440/ 380	Voltage (V)	230	230	230
Water flow Qmax/Qiec (l/h)440/ 380440/ 380440/ 380Hose length (m)686Max. inlet temperature (°C)404040Dimensions (L x W x H) (mm)305 x 295 x 885305 x 295 x 885305 x 295 x 885Weight (kg)15.815.815.815.8Technical specificationsC135.1-6l X-TRAC135.1-8l X-TRAC135.1-8l X-TRAPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Water flow Qmax/Qiec (l/h)440/ 380440/ 380440/ 380	Rated power (kW)	1.7	1.7	1.7
Hose length (m) 6 8 6 Max. inlet temperature (°C) 40 40 40 Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Weight (kg) 15.8 15.8 15.8 Technical specifications C 135 1-61 X-TRA C 135 1-81 X-TRA C 135 1-61 PAD X-TRA EU Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440,380 440,380 440,380	Power consumption (A)	7.4	7.4	7.4
Max. inlet temperature (°C)4040Dimensions (L x W x H) (mm)305 x 295 x 885305 x 295 x 885Weight (kg)15.815.815.8Technical specificationsC 135.1-61 X-TRA EUC 135.1-81 X-TRA EUC 135.1-81 X-TRA C 135.1-81 X-TRAC 135.1-81 X-TRA C 135.1-81 X-TRAPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Water flow Qmax/Qiec (l/h)440/380440/380440/380	Water flow Qmax/Qiec (I/h)	440/ 380	440/ 380	440/ 380
Dimensions (L x W x H) (mm) 305 x 295 x 885 305 x 295 x 885 305 x 295 x 885 Weight (kg) 15.8 15.8 15.8 Technical specifications C 135 1-61 X-TRA EU C 135 1-81 X-TRA EU C 135 1-81 X-TRA EU C 135 1-81 X-TRA EU Pump pressure (bar/MPa) Max 135 / max 13.5 Max 135 / max 13.5 Max 135 / max 13.5 Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (I/h) 440/ 380 440/ 380 440/ 380	Hose length (m)	6	8	6
Weight (kg)15.815.815.8Technical specificationsC 135.1-61 X-TRA EUC 135.1-81 X-TRA EUC 135.1-61 PAD X- TRA EUPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Water flow Qmax/Qiec (I/h)440/380440/380440/380	Max. inlet temperature (°C)	40	40	40
Technical specificationsC 135.1-6l X-TRA EUC 135.1-6l PAD X- TRA EUPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230Rated power (kW)1.71.7Power consumption (A)7.47.4Water flow Qmax/Qiec (I/h)440/380440/380	Dimensions (L x W x H) (mm)	305 x 295 x 885	305 x 295 x 885	305 x 295 x 885
Federinical specificationsEUEUTRA EUPump pressure (bar/MPa)Max 135 / max 13.5Max 135 / max 13.5Max 135 / max 13.5Voltage (V)230230230Rated power (kW)1.71.71.7Power consumption (A)7.47.47.4Water flow Qmax/Qiec (I/h)440/380440/380440/380	Weight (kg)	15.8	15.8	15.8
Voltage (V) 230 230 230 Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (I/h) 440/380 440/380 440/380	Technical specifications	C 135.1-6I X-TRA EU		
Rated power (kW) 1.7 1.7 1.7 Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (l/h) 440/380 440/380 440/380	Pump pressure (bar/MPa)	Max 135 / max 13.5	Max 135 / max 13.5	Max 135 / max 13.5
Power consumption (A) 7.4 7.4 7.4 Water flow Qmax/Qiec (I/h) 440/380 440/380 440/380	Voltage (V)	230	230	230
Water flow Qmax/Qiec (I/h) 440/380 440/380 440/380	Rated power (kW)	1.7	1.7	1.7
	Power consumption (A)	7.4	7.4	7.4
Hose length (m) 6 8 6	Water flow Qmax/Qiec (I/h)	440/ 380	440/ 380	440/ 380
	Hose length (m)	6	8	6



All information provided in this document is subject to change without prior notice

The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

Technical specifications	C 135.1-6I X-TRA EU	C 135.1-8I X-TRA EU	C 135.1-6i PAD X- TRA EU
Max. inlet temperature (°C)	40	40	40
Dimensions (L x W x H) (mm)	305 x 295 x 885	305 x 295 x 885	305 x 295 x 885
Weight (kg)	15.8	15.8	15.8
Technical specifications		C 135.1-6i PAD X- TRA UK	C 135.1-8i PAD X- TRA EU
Pump pressure (bar/MPa)		Max 135 / max 13.5	Max 135 / max 13.5
Voltage (V)		230	230
Rated power (kW)		1.7	1.7
Power consumption (A)		7.4	7.4
Water flow Qmax/Qiec (I/h)		440/ 380	440/ 380
Hose length (m)		6	8
Max. inlet temperature (°C)		40	40
Dimensions (L x W x H) (mm)		305 x 295 x 885	305 x 295 x 885
Weight (kg)		15.8	15.8

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
۲	Car brush head	128500463	0	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	0
8	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	0
	ROTARY BRUSH	6410762	0	0	0	0



The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK
	ROTARY BRUSH	126411395	0	0	0	0
Accessory						
	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	0
0	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	0	0
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•	•
	G3 LANCE COMPLETE	126481134	0	•	•	•
Ç	INLET SUCTION HOSE 3M	128500673	0	0	0	0
	MULTI ANGLE ADAPTER	6411138	0	0	0	0
	MULTI BRUSH	128470456	0	0	0	0
.	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
	NILFISK PATIO ACCESSORY	128500702	0	0	0	•
10	NILFISK POWER PATIO	128500955	0	0	0	O



All information provided in this document is subject to change without prior notice

	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK
	NILFISK WATER FILTER	128500674	0	0	0	0
1 M	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0	0
	WALL HOOK	106411386	0	0	0	0
6	WATER SUCTION KIT	126411387	0	0	0	0
Nozzle - High	Pressure Washer					
ø	C&C CAR NOZZLE	6411136	0	0	0	0
	PR TORNADO TURQUOISE	126481118	0	•	•	•
-	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	0
Hose and Co	nnection					
0	8M STANDARD HOSE	128500080	0		•	
Q	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0	0



	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA UK	C 135.1-8I X- TRA UK	C 135.1-6i P X-TRA UK
Q	HOSE 6M	126481138	0	•		•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0
Accessory Kit						
	MULTI BRUSH KIT	128470459	0	0	0	o
00 0 0	O-RING KIT CONSUMER HPW	128500292	0	0	0	0

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
Brush						
	AUTOBRUSH ALONE	6411131	0	0	0	0
۲	Car brush head	128500463	0	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	0	0	•
8	Garden brush head	128470457	0	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0	O
	ROTARY BRUSH	6410762	0	0	0	O



	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
	ROTARY BRUSH	126411395	0	O	O	0
Accessory		1				
7	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•	•
9	DRAIN AND TUBE 8M	128500461	0	0	0	•
\bigcirc	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	0	0
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•	•
	G3 LANCE COMPLETE	126481134	0	•	•	٠
Ç	INLET SUCTION HOSE 3M	128500673	0	0	O	O
	MULTI ANGLE ADAPTER	6411138	0	0	0	0
	MULTI BRUSH	128470456	0	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0	0
	NILFISK PATIO ACCESSORY	128500702	0	O	0	•



	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
19	NILFISK POWER PATIO	128500955	0	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0	0
À LL	ROOF CLEANER	128470040	0	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0	0
	WALL HOOK	106411386	0	0	0	0
^ "	WATER SUCTION KIT	126411387	0	0	0	0
Nozzle - High	Pressure Washer					
<i>•</i>	C&C CAR NOZZLE	6411136	0	O	O	0
	PR TORNADO TURQUOISE	126481118	0	•	•	•
9	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0	O
Hose and Co	nnection					
O	8M STANDARD HOSE	128500080	0		•	



The handy all-round, high-pressure washer. With full power flexibility and extra tough induction motor for frequent or larger cleaning tasks.

	Accessories	Ref. no.	Min. required	C 135.1-6I X- TRA EU	C 135.1-8I X- TRA EU	C 135.1-6i PAD X-TRA EU
Ø	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0	0
Q	HOSE 6M	126481138	0	•		•
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0	0
Accessory Kit			1			
.	MULTI BRUSH KIT	128470459	0	0	0	0
•• 000 0	O-RING KIT CONSUMER HPW	128500292	0	0	0	0

ullet Standard equipment, $^{\bigcirc}$ Supplementary accessories, $^{\square}$ Mountable equipment

	Accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
Brush					
	AUTOBRUSH ALONE	6411131	0	0	0
•	Car brush head	128500463	0	0	0
	FIXED BRUSH SHORT NILFISK SP	128500685	0	•	•
8	Garden brush head	128470457	0	0	0
	RIM BRUSH HEAD	128470458	0	0	0



	Accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
	ROTARY BRUSH	6410762	0	0	0
	ROTARY BRUSH	126411395	0	0	0
Accessory					
7	C&C FOAMSPRAYER WITH BOTTLE	128500077	0	•	•
9	DRAIN AND TUBE 8M	128500461	0	•	•
0	DRAIN AND TUBE CLEANER ALTO	6410766	0	0	0
	G3 GUN WITH INTERMEDIATE TUBE	126481132	0	•	•
	G3 LANCE COMPLETE	126481134	0	•	•
Ç	INLET SUCTION HOSE 3M	128500673	0	0	0
	MULTI ANGLE ADAPTER	6411138	0	0	0
	MULTI BRUSH	128470456	0	0	0
	NILFISK C&C SUPER FOAM SPRAYER	128500938	0	0	0



	Accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
	NILFISK PATIO ACCESSORY	128500702	0	•	•
10	NILFISK POWER PATIO	128500955	0	0	0
	NILFISK WATER FILTER	128500674	0	0	0
1 III	ROOF CLEANER	128470040	0	0	0
	UNDERCHASSIS SPRAY LANCE	6410763	0	0	0
Ý	VSB SET - GREEN	6410891	0	0	0
	WALL HOOK	106411386	0	0	0
6	WATER SUCTION KIT	126411387	0	0	0
Nozzle - High	Pressure Washer				
ø	C&C CAR NOZZLE	6411136	0	0	0
	PR TORNADO TURQUOISE	126481118	0	•	•
-1	UNDER CARRIAGE SPRAY NOZZLE	6411135	0	0	0
Hose and Co	nnection				



	Accessories	Ref. no.	Min. required	C 135.1-6i PAD X-TRA UK	C 135.1-8i PAD X-TRA EU
0	8M STANDARD HOSE	128500080	0		•
\bigcirc	EXT. HOSE 7 M - QUICK COUPLING	106411346	0	0	0
Q	HOSE 6M	126481138	0	•	
	NILFISK BA VALVE COMP. GARDENA	106411177	0	0	0
Accessory Kit					
.	MULTI BRUSH KIT	128470459	0	0	0
00 0 00	O-RING KIT CONSUMER HPW	128500292	0	0	0

