



City Ranger 2250 Snow Sweeper

The snow sweeper is perfect when used with the first snow fall of winter. It can completely remove snow to a depth of 15 cm – even when the terrain is uneven, keeping paths clear and dry.

The snow sweeper is centred and fitted onto the front of the utility machine. It has a full working width of 1,220 mm. It can sweep right into walls and bases without damaging the machine or building – and of course it can be combined with a salt and sand spreader fitted on the back, so that areas being swept can simultaneously be made safe and passable. Two jobs done at once. Twice as effective.

The operator has full visibility, making driving and manoeuvring easy.

The snow sweeper is designed with an integrated supporting strut. The support strut protects the snow sweeper when it is stored and makes it easy to move.




When you change attachments, the City Ranger 2250 hydraulic hoses are connected at the turn of a handle!



Technical data

Snow Sweeper



Technical specifications

The trapeze-mounting ensures the snow sweeper remains clear of the utility machine's wheels at all times, whatever the angle

The snow sweeper automatically turns with the utility machine — always sweeping in front of the utility machine's wheels

The snow sweeper brushes best, saving energy and minimising wear-and-tear, when only the ends of the brush are sweeping the surface

Attaching and detaching is quick, and no tools are needed

The snow sweeper is easy to clean

Valve for reversing, so the brushes can turn in both directions and draw snow to them in narrow spaces where the utility machine cannot turn

Adjustable speed of the snow sweeper is standard

Extra equipment

Brush guard to protect surroundings

Dimensions

Attached:

Length	3,260 mm
Width	1,220 mm
Height	1,960 mm

Storage dimensions:

Length	820 mm
Width	1,220 mm
Height	650 mm

Technical data:

Weight	104 kg
Clearing width	1,140-1,220 mm
Sweeping capacity	10-12,000 m ²
Brush cylinder rpm	0-255 rpm
Brush diameter	550
Ground clearance below brush	420

CE certified according to EU Directive

Your Nilfisk Outdoor Dealer